

# Cruach Clenamacrie Wind Farm FEI Appendix 6.1 Proposed Apportioned Noise Limits



# FEI Technical Appendix 6.1

Cruach Clenamacrie Wind Farm

Client: Voltalia UK Ltd Reference: C5676-1404

Version 1.0

August 2025







## **Report Prepared for:**

Voltalia UK Ltd

### **Author:**

Paul Hawthorne (Green Cat Renewables Ltd)

Version	Reviewed by (Date)	Approved by (Date)	Date of Issue	Details
V1.0	Harry Matthews (07/07/2025)	Cameron Sutherland (14/07/2025)	14/07/2025	First Draft
V2.0			31/07/2025	Client Draft
V2.1	Merlin Garnett (18/08/2025)	Cameron Sutherland (26/08/2025)	26/08/2025	Final Issue



# **Table of Contents**

6	Technical Appendix 6.1	1
6.1	Proposed Apportioned Noise Limits	1



# 6 Technical Appendix 6.1

# 6.1 Proposed Apportioned Noise Limits

As the adopted ETSU-R-97 limits apply to cumulative immissions from both the Proposed Development and Corr Chnoc Wind Farm, it is suggested that each development be assigned apportioned limits, as discussed in section 5.4 of the IoA Good Practice Guide in relation to concurrent applications. The following methodology was applied to both projects:

Apportioned noise limits are calculated by:

- determining available headroom above predicted cumulative immission levels;
- assigning equal increases in immission for each project above predicted levels to a maximum of +2dB; and
- adopting the expanded immission levels as apportioned limits.

The resulting apportioned limits for the Proposed Development, applicable for both daytime and night-time periods, are given in **Table 6.1**. The apportioned limits are then tested against the adopted ETSU-R-97 limits to ensure compliance.

Table 6.1: Proposed Development apportioned limits (all assessment periods)

NAL	Location	Standardised V10 wind speed (m/s)										
		4	5	6	7	8	9	10	11	12		
NAL4	Dorran Cottage	24.9	29.5	33.7	34.8	34.9	35.2	35.5	35.6	35.6		
NAL5	Glenamachrie	25.4	30.0	34.2	35.3	35.4	35.7	36.0	36.1	36.1		

The same approach has been applied to the Corr Chnoc immission levels, shown in Table 6.2

Table 6.2: Corr Chnoc apportioned limits (all assessment periods)

NAL	Location	Standardised V10 wind speed (m/s)									
		4	5	6	7	8	9	10	11	12	
NAL4	Dorran Cottage	25.8	30.4	34.6	35.7	35.8	36.1	36.4	36.5	36.5	
NAL5	Glenamachrie	25.2	29.8	34.1	35.1	35.3	35.5	35.8	35.9	35.9	

To confirm whether the proposed apportioned limits for each development can be accommodated, the limits were summed with the proposed Corr Chnoc and tested for compliance with the adopted ETSU-R-97 limits. Exceedance of limits is shown below in **Table 6.3** and **Table 6.4**.



Table 6.3: Exceedance of total daytime ETSU-R-97 limits

NAL	Location	Standardised V10 wind speed (m/s)										
		4	5	6	7	8	9	10	11	12		
NAL4	Dorran Cottage	-8.7	-4.8	-1.2	-0.9	-1.6	-2.2	-3.1	-4.3	-5.9		
NAL5	Glenamachrie	-8.8	-4.9	-1.2	-0.9	-1.7	-2.3	-3.2	-4.4	-6.0		

Table 6.4: Exceedance of total night-time ETSU-R-97 limits

NAL	Location	Standardised V10 wind speed (m/s)									
		4	5	6	7	8	9	10	11	12	
NAL4	Dorran Cottage	-14.6	-10.0	-5.8	-4.8	-4.6	-4.3	-4.0	-4.7	-6.8	
NAL5	Glenamachrie	-14.7	-10.1	-5.8	-4.8	-4.7	-4.4	-4.1	-4.8	-6.9	

The results given in **Table 6.3** and **Table 6.4** demonstrate that the proposed apportioned limits can be accommodated cumulatively in accordance with ETSU-R-97 and the IoA Good Practice Guide.



## **Registered Office**

Green Cat Renewables Stobo House Roslin Midlothian EH25 9RE

+44 (0) 131 541 0060

info@greencatrenewables.co.uk www.greencatrenewables.co.uk